Transducer Specifics

C611-2



C361-2



C321-2



L743-2



V563-2



General:

Imaging mode: B, 2B, 4B, B+M, M, and PW
Gray scale levels: 256
Display: 12.1" TFT-LCD
Transducer frequency: 2.0-10.0MHZ
Transducer connector: 2 standard
Beam Forming:
Phase Inversion Harmonic Imaging
Multi-Beam Technology
Synthetic Receiving Aperture
Dynamic Receiving Focusing
Real-time Dynamic Aperture
Dynamic Frequency Scanning
Dynamic Apodization
Scanning angle:
Up to 155 degrees (transducer dependent)
Scanning depth (mm):
From 19 to 324 (transducer dependent)

Functions:

Cine loop: 256-frame bidirectional cine-loop
Zoom: x1.0, x1.2, x1.4, x1.6, x2.0, x2.4, x3.0, x4.0 in distance
Panoramic zoom in real-time and freeze
Storage media:
Built-in Flash, internal large capacity data storage
Built-in image archive:
504MB built-in image storage
Body marks: 40 types
Transducer auto-detection

Display:

Date, Time, Probe Frequency, Frame Rate, Host, ID, Hospital Name, Depth, Frame Rate, Exam Type, Measurement Values, Gain, IP, Body Marks, Annotations, Probe Position

Others:

Peripheral ports:
S-video output: 1
Video output: 1
VGA output: 1
USB port: 2
Ethernet port: 1
Remote control: 1
Footswitch port: 1

Power supply: 100V-240V ~ 50Hz/60Hz
Lithium battery: Continuous operation for up to 2 hours
Dimensions: 330mm (13.0") (L) x220mm (8.7") (W) x320mm (12.6") (H)
Net weight: 7.1kg (15.7 lb)

Imaging Processing:

Pre-processing: Dynamic Range
Frame Persist
Gain
8-segment TGC adjustment
IP (Imaging Process)
Post-processing: Gray map
Speckle Reduction Technology
Pseudo-color
Gray Auto Control
Black/white invert
Left/right invert
Up/down invert
Image rotation at 90° interval

Measurement & Calculation:

B-mode: Distance, circumference, area, volume, ratio % stenosis, histogram, and angle
M-mode: Distance, time, slope, and heart rate
Doppler: Time, heart rate, velocity, acceleration, trace, and RI
Software packages:
Canine, feline, equine, bovine, ovine

Standard configurations:

DUS 60 VET main unit
12.1" TFT-LCD monitor
Two transducer connectors
Pulsed wave Doppler
Multiple-pseudo-color Imaging
256-frame cine loop memory
504MB built-in image storage
Two USB ports
Measurement & calculation software packages

Options:

Micro-convex array transducer:
C611-2 (5.5/6.5/7.5/H9.0/H9.4MHz)
Micro-convex array transducer:
C321-2 (2.5/3.5/4.5/H5.0/H5.4MHz)
Convex array transducer:
C361-2 (2.5/3.5/4.5/H5.0/H5.4MHz)
Linear array transducer:
L761-2 (6.5/7.5/8.5/H9.0/H9.4MHz)
Linear array transducer:
L743-2 (6.5/7.5/8.5/H9.0/H9.4MHz)
Endorectal transducer:
V563-2 (4.5/5.5/6.5/H8.0/H8.4MHz)
Transducer needle-guide brackets
Large capacity data storage
Video printer
Laser printer
Inkjet printer
Footswitch
Li-ion battery
Mobile trolley
Hand-carry bag
DICOM 3.0
UMS100 workstation software

About Edan

Edan is a healthcare company dedicated to improving the human condition around the world by delivering value-driven, innovative and high-quality medical products and services. For over 20 years, Edan has been pioneering a comprehensive line of medical solutions that address a broad range of healthcare practices including:

- Diagnostic ECG
- Patient Monitoring
- OB/GYN
- Ultrasound Imaging
- Point-of-Care Testing
- *In-Vitro* Diagnostics
- Veterinary

Healthcare professionals around the world depend on Edan's breakthrough medical technologies and outstanding customer support.

EDAN
A world of potential

U.S. and Canada inquiries:
EDAN Diagnostics, Inc. | 9833 Pacific Heights Blvd., Suite E/F
San Diego, CA 92121-4707 | +1.858.750.3066
www.edandiagnostics.com | edan-info@edandiagnostics.com

Inquiries outside of the U.S. and Canada:
Edan Instruments, Inc. | No.15 Jinhui Rd., Jinsha Community,
Kengzi Subdistrict, Pingshan District, Shenzhen | 518122 P.R. China
+86.755.26898326 | www.edan.com.cn | info@edan.com.cn

© 2019 Edan Instruments, Inc. All rights reserved. Features and specifications are subject to change without prior notice. No reproduction, copy or transmission may be made without written permission.
Not all products or features are available in all territories, contact Edan for local availability.

ENG-US-DUS 60 VET-V2.5-20190222

DUS 60 VET

Veterinary Digital Ultrasonic Diagnostic Imaging System

Superior Value and Versatility



EDAN
A world of potential

DUS 60 VET

Superior Value and Versatility



Efficient

Compact

Versatile



Powerful technologies to increase your diagnostic confidence

- Phase Inversion Harmonic Imaging technology provides best-in-class image quality
- PW Doppler supplies physiologic information for increased diagnostic value
- Five-frequency transducers increases versatility



Go anywhere you need to go

- Compact and lightweight design for excellent mobility
- Built-in battery provides up to 2 hours of point-of-care imaging
- Large capacity data storage



Intuitive user-friendly design

- One touch image optimization via smart IP key
- Backlit, easy-to-use control panel
- User-defined keys to customize your work-flow



Practical tools enhance efficiency

- Intelligent 8-segment TGC for precise adjustment
- Multi-format data transfer via USB and DICOM
- Multiple-pseudo-color options enhance image presentation

The DUS 60 VET is an impressive new compact ultrasound system, providing superb value and quality across the entire range of applications. The addition of PW Doppler increases diagnostic information content.



Canine Kidney



Canine Gall Bladder



Canine Bladder



Canine Renal Stone



Canine Heart